



**GL205**



**GL205A**

MODEL	GL205	GL205A
Motor power	0.75kw/1.1kw	0.75kw/1.1kw
Power supply	110V/220V/380V	110V/220V/380V
Max.wheel diameter	41"(1040mm)	41"(1040mm)
Max.wheel width	14"(400mm)	14"(400mm)
Outside clamping	10"~22"	10"~22"
inside clamping	12"~24"	12"~24"
Air supply	8bar	8bar
Bead break porec	2500kg	2500kg
Noise level	<70dB	<70dB
Carton size	960mm*760mm*850mm(Main body) 900mm*400mm*870mm(Auxiliary Arm)	960mm*760mm*950mm(Main body) 900mm*400mm*870mm(Auxiliary Arm)

#### GL205

- 1.The side suspends the arm type.
- 2.Enlarge, Canadian thick box body, working strength multiplication.
- 3.24 " the Canadian bulk lots and the high efficiency electrical machinery, are suitable for disassembling are bigger, a wider tire.
- 4.Auxiliary helps the system to cause the knocked-down and assemble width flat tire to be extremely quick, reduces effort.

#### GL205A

- 1.The side suspends the arm type.
- 2.Enlarge, Canadian thick box body, working strength multiplication.
- 3.24 " the Canadian bulk lots and the high efficiency electrical machinery, are suitable for disassembling are bigger, a wider tire.
- 4.Auxiliary helps the system to cause the knocked-down and assemble width flat tire to be extremely quick, reduces effort.
- 5."A" fast gasification system instantaneous gasification, thus causes the flat quite small vacuum bead reason and the wheel felloe pastes rapidly is closed tightly.